
Meridian 1

ISDN Basic Rate Interface

Product Description

Document Number: 553-3901-100
Document Release: Standard 5.00
Date: October 1997

© 1992, 1997
All rights reserved

Printed in Canada

Information is subject to change without notice. Northern Telecom reserves the right to make changes in design or components as progress in engineering and manufacturing may warrant. This equipment has been tested and found to comply with the limits for a Class A digital device pursuant to Part 15 of the FCC rules, and the radio interference regulations of Industry Canada. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses and can radiate radio frequency energy, and if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at their own expense.

SL-1 and Meridian 1 are trademarks of Northern Telecom.

Revision history

October 1997

Issue 5.00 released as Standard for Generic X11 Release 23.

August 1996

Issue 4.00 released as Standard for Generic X11 Release 22.

December 1995

Issue 3.00 released as Standard for Generic X11 Release 21B.

July 1995

Issue 2.00 released as Standard for Generic X11 Release 21A.

December 1994

Issue 1.00 released as Standard for Generic X11 Release 20.

July 1994

Standard version released for Generic X11 Release 20.0x.

July 1993

Standard version released.

Contents

About this guide	9
Applicability of this guide	9
How this guide is organized	9
Related documents	10
Functional description	11
ISDN Basic Rate Interface overview	11
General ISDN BRI capabilities	13
The OSI model	14
ISDN BRI line access	16
S/T interface configured for line access	16
U interface configured for line access	18
ISDN BRI Packet data transmission	21
Packet data transmission using the DPN-100	21
Packet data transmission using the Meridian 1 Packet Handler ...	24
ISDN BRI trunk access	28
ISDN BRI Local Exchange/CO/DID connectivity	29
ISDN BRI MCDN Tie trunk connectivity	38
ISDN BRI QSIG connectivity	41
Engineering guidelines	43
Hardware Requirements	43
line application	43
Packet handling	46
trunk application	51
Hardware functional descriptions	53

Physical capacity	66
Physical capacity without the BRSC	66
Physical capacity with the BRSC	68
Memory capacity	69
Protected data store	69
Unprotected data store	72
ISDN BRI configuration guidelines	76
Physical parameters	76
Functional parameters	81
Transmission characteristics	85
SILC DSL line configuration	85
SILC DSL trunk configuration	97
UILC DSL line configuration	98
Terminal addressing and service profile assignment	103
ISDN BRI terminal interface specification	110
S/T interface specification	110
U interface specification	112
Compatible ISDN BRI terminals	113
Features on ISDN BRI	115
Introduction	115
ISDN BRI specific features	116
Calling Line Identification Presentation and Restriction	116
ISDN BRI National ISDN-1 Conference	117
ISDN BRI circuit-switched data calls	120
ISDN BRI Special Call Forward Busy	124
ISDN BRI Special Hunting	124
ISDN BRI ETSI Call Forwarding Unconditional	125
ISDN BRI ETSI Conference	129
ISDN BRI National ISDN-1 Call Forward All Calls	131
ISDN Basic Rate Interface Connected Line Presentation/Restriction	
134	
NI-1 BRI Compliance Enhancements	137
Set-based ISDN BRI features on Meridian 1 ISDN BRI terminals	139
Generic X11 features	140

ISDN BRI Lines — Generic X11	140
Features supported by ISDN BRI as a Line	163
Features partially supported by ISDN BRI as a line	168
ISDN BRI Trunk Access features: Generic X11	176
ISDN PRI features interaction with ISDN BRI	176
ISDN PRI features not supported	176
Generic X11 International features — lines and trunks	178
Generic X11 International features interaction	178
Generic X11 International features partially supported	193
List of terms	209